# **KINZE PLANTER CHECKLIST**

| Serial Number:   |  |
|------------------|--|
| Model:           |  |
| Inspection Date: |  |
| Inspected By:    |  |









**V Precision Planting**®

## **Hitch Styles**

| Hitch 2 Point System:   |
|---|
| □ 2 point assembly  |
| ☐ Pivot pins  |
| ☐ Support stands  |
| ☐ HYD hose clamp assembly   |
| ☐ HYD hoses for wear/leaking  |
| ☐ HYD hose protective covering for wear/secure                              |
| □ Electrical harnesses for chaffing   |
| □ Electrical connectors clean/secure, not damaged                           |
| ☐ Draft arm pivot assemblies for wear, bolts tight                          |
| □ Draft arm tubes for damage  |
| ☐ Grease/lubricate per operators manual                                     |
| Hitch Hydraulic Tongue Style:   |
| (3700/3800)   |
| ☐ Clevis hitch bearing for wear   |
| ☐ Pivot bolts tight   |
| ☐ Upper & lower support arms pivot pins                                     |
| ☐ Upper arm hydraulic cylinder attachment pins for wear                     |
| ☐ HYD cylinder for leaks  |
| ☐ HYD support holder secure   |
| ☐ HYD hoses for wear/leaking  |
| ☐ HYD hoses protective covering for wear/secure                             |
| ☐ Support stands & pins   |
| ☐ Electrical harnesses for chaffing   |
| ☐ Connectors clean/secure, not damaged                                      |
| ☐ Draft arms pivot assemblies for wear, bolts tight, tubes for damage       |
| ☐ Welds/structural members for cracks                                       |
| ☐ Grease/lubricate per operators manual                                     |
| Hitch Fixed Tongue Style:   |
| ☐ Clevis hitch for wear, pivot bolt tight                                   |
| ☐ Safety Chain no damage, correctly routed and attachment bolts tight       |
| ☐ Support jack & attachment pin no damage                                   |
| ☐ HYD hose holder assembly secure not broken                                |
| ☐ HYD hose mounting brackets along tongue securely holding hoses, no damage |
| ☐ HYD hose for wear/leaking   |
| ☐ HYD hose protective cover secure, no damage                               |
| ☐ Electrical: Harnesses for chaffing, connectors clean/secure, no damage    |
| ☐ Hitch frame secure, no cracks, no loose bolts, not bent                   |
| ☐ Welds/structural members for cracks                                       |
| ☐ Grease/lubricate per operators manual                                     |

## **Lift &Twist System**

| Hitch Tongue Assembly:   |
|--|
| ☐ Clevis hitch for wear, pivot bolt tight                                |
| ☐ Safety Chain not damaged, correctly routed and attachment bolt tight   |
| ☐ Hitch assembly to tongue bolts tight                                   |
| ☐ Support jack for damage & attachment pins                              |
| ☐ HYD hose holder assembly secure not broken                             |
| ☐ HYD hose for wear/leaking  |
| ☐ HYD hose protective cover secure, damage                               |
| ☐ Electrical: Harnesses for chaffing, connectors clean/secure, damage    |
| ☐ Forward bar support bolts tight,                                       |
| ☐ Folding latch assembly wear/damage, cylinder for leaks                 |
| ☐ Tongue sliding pads for wear, secure, correctly adjusted               |
| ☐ A-frame assembly not damaged, tight                                    |
| ☐ A-frame pivot bolts tight  |
| ☐ A-frame HYD hoses not damaged, routed correctly, secured               |
| ☐ A-frame electrical harness not damaged, routed correctly, secured      |
| ☐ Grease/lubricate per operators manual                                  |
|  |
| Center Tower/ Rotating System:   |
| ☐ Tower sliding pads for wear and correctly adjusted                     |
| ☐ Tower welds/structural members for cracks                              |
| ☐ Tower upper latch assembly not damaged                                 |
| ☐ Tower rotating cylinder not leaking                                    |
| ☐ HYD hoses not damaged, routed correctly, secure                        |
| ☐ HYD hose protective cover not damaged and secure                       |
| ☐ Electrical harness not damaged, routed correctly, secure               |
| ☐ HYD hose guideway assembly not damaged, secure                         |
| ☐ HYD lift cylinders not leaking   |
| ☐ Transport tires not damaged, correct pressure                          |
| ☐ Weight transfer cylinder not damaged or leaking                        |
| ☐ Grease/lubricate per operators manual                                  |
|  |
| Stack Folding:   |
| ☐ 3 point pins for damage  |
| ☐ Support stands & attachment pins for damage                            |
| ☐ HYD hose holder assembly secure not broken                             |
| ☐ HYD hose for wear/leaking  |
| ☐ HYD hose protective cover secure, damage                               |
| ☐ Electrical: Harnesses for chaffing, connectors clean/secure, no damage |
| ☐ Folding cylinders, not leaking or damaged                              |
| ☐ Folding cylinder pivot pins for wear                                   |
| ☐ Folding pivot pins for wear  |
| Grease/lubricate per operators manual                                    |

#### **Frame & Transport Systems**

### Center Section: □ Welds/structural members for cracks ☐ Hardware/bolts tight ☐ Hydraulic cylinders for leaks and damage ☐ HYD cylinders attachment pins for wear/damage ☐ HYD hoses not damaged, routed correctly, secured ☐ Electrical harness not damaged, routed correctly, secured ☐ Folding hinge points not damaged, no worn pins/bushings ☐ Bulk fill tanks not damaged, secure ☐ Seed delivery manifold not damaged, cleaned out ☐ Seed manifold agitation motor operational ☐ Seed delivery hoses/tubes not damaged, correctly routed, secured ☐ Seed delivery blower not damaged, clean, large hose not damaged & secured ☐ Seed delivery blower HYD motor not leaking, hoses not damaged/leaking, secured ☐ Transport tires correct pressure Frame Row Unit Mounting Assembly: ☐ Inspect welds/structural members for cracks ☐ Flex points pins/bushings for wear/damage ☐ Folding points pins/bushings for wear/damage ☐ Vacuum blower not damaged, blades clean, bolts tight ☐ Vacuum blower motor not leaking ☐ Vacuum mounting brackets not damaged, secured ☐ Vacuum blower HYD hoses not damaged, secured ☐ Vacuum main line, plastic tube or metal frame not damaged, leaking, secured ☐ Vacuum row hoses not damaged, routed correctly, secured ☐ Marker cylinders not leaking, HYD hoses not leaking or damaged, pivot pin for wear ☐ Marker HYD hoses not leaking or damaged ☐ Marker pivot pins for wear ☐ Markers disc blades for wear, bolts tight ☐ Row unit "U" bolts not broken, nuts tight, row width correct ☐ Grease/lubricate per operators manual

| Frame Lift Assembly:   |
|--|
| ☐ Inspect welds/structural members for cracks  |
| ☐ Pivot pins and bushings for wear   |
| ☐ Wheel bearings tight and greased   |
| ☐ Tires for damage, correct pressure, lug nuts torqued   |
| ☐ Lift cylinders not leaking or damaged  |
| ☐ Lift cylinders HYD hoses not leaking and secure  |
| ☐ Lift cylinders pivot pins for wear   |
| ☐ Grease/lubricate per operators manual  |
| Drives:  |
| ☐ Main drive tires not damaged, correct pressure   |
| ☐ Contact drives tire not damaged, correct pressure  |
| Contact Drive Chains for wear, not rusty   |
| <ul><li>□ Sprockets for wear &amp; alignment</li><li>□ Idlers for wear, not damaged, correct tension &amp; alignment</li></ul> |
| ☐ Hydraulic drives, not leaking, operational check   |
| ☐ Hydraulic drive hoses not leaking, no damage   |
| ☐ Hydraulic drive chains, for wear, not rusty, tension as needed   |
| ☐ Grease/lubricate per operators manual  |
| Transmissions:   |
| □ shafts not bent or damaged   |
| ☐ Bearings run smoothly  |
| ☐ Chains not rusty   |
| Sprockets no damaged teeth   |
| <ul><li>☐ Shear Pins not damaged &amp; extra replacements</li><li>☐ Grease/lubricate per operators manual</li></ul>            |
| Grease/fublicate per operators maridar   |
| Main Hex Shaft:  |
| ☐ Shaft not bent or damaged  |
| Shaft section locking collars tight  |
| <ul><li>□ Bearings run smoothly</li><li>□ Sprockets not damaged</li></ul>  |
| ☐ Hex shaft flex drives for wear, not damaged  |
| ☐ Row Clutches not damaged, service and operational check  |
| ☐ Hex shaft flex point "U" joint knuckles  |
| ☐ Grease/lubricate per operators manual  |

# **Electrical & Seed Monitoring**

| Wiring Harnesses:   |
|---|
| ☐ Fold/unfold control box for damage  |
| □ Fold/unfold harness for damage, secure as needed  |
| ☐ Fold/unfold HYD manifold, inspect solenoid valves, not leaking, operational check   |
| $\square$ Seeding harness inspect for damage to outer sheathing ,secure as needed   |
| $\square$ Smart connector, inspect for damage, secure as needed, perform operational check  |
| ☐ Swath control harnesses, inspect for damage, secure as needed   |
| <ul> <li>☐ Hydraulic drive control harnesses, inspect for damage, secure as needed</li> <li>☐ Power tractor harness from battery to hitch, inspect for damage</li> <li>☐ Power harness to PDM, inspect connectors for damage, corrosion on pins, sockets</li> <li>☐ CAN harness to PDM, inspect connectors for damage, corrosion on pins, sockets</li> <li>☐ Apex power harnesses from PDM to backbones, inspect for damage, secure as needed</li> <li>☐ Backbone harnesses, inspect for damage, corrosion on pins, sockets, secure as needed</li> <li>☐ CAN harness to PDM, inspect connectors for damage, corrosion on pins, sockets</li> <li>☐ PDM, mounting secure, no damage</li> <li>☐ Alternator, mounting secure, no damage</li> <li>☐ Alternator electrical harness, no damage, connectors tight</li> <li>☐ Perform an operational check of all systems</li> </ul> |
| Sensors/Switches:  Radar sensor for damage, clean, operation check Seed Tube Sensors for damage, clean, operation check Hex shaft Rotation Sensors no damage, operation check Wheel speed Rotary Height Switch not damaged/operational check Frame folding switches no damage   |
| Transport System:  ☐ Safety latches inspect operation check & adjust ☐ Wheel bearings for wear and grease ☐ Mud scrapers for wear and adjust ☐ Lug nuts/Bolts and Spindle Bolts torqued ☐ Hazard lights no damage, operation check ☐ Toolbar Height, 20 in to 22 in ☐ Lubrication and grease per operator's manual  |
| Safety:  ☐ Warning Lights, operate correctly  ☐ SMV Sign, visible and reflective  ☐ Safety Warning Signs, condition/clean  ☐ Reflectors/Reflective Decals, condition/clean  |

# **Fertilizer Equipment**

| Tanks:  ☐ Inspect welds/structural support members for cracks ☐ Delivery hose for damage, not leaking, secure ☐ Fill hose for damage, not leaking, secure ☐ Valves for damage, not leaking, lubricate ☐ Filter system for damage, not leaking, secure        |
|--|
| Squeeze Pump:  Metering Hoses, not leaking, damaged, correct routing, secure Bushings and rollers for condition Roller plate and springs for condition Drive chain rusty, damage, alignment and lubrication  |
| Piston Pump:  ☐ Case/Hose Connections not damage/leaking ☐ Oil level, check/replenish to correct level ☐ Drive chain and tires, not damaged, correct pressure, lubrication   |
| Centrifugal Pump:  ☐ Case/Hose Connections not damage/leaking ☐ HYD drive motor not leaking, Note: Running pump dry will damage seal!!! ☐ HYD hoses for damage, not leaking, correct routing, secure ☐ Electrical connectors for damage, no corrosion, clean |

### Parts Needed/ Notes:

#### Parts Needed/ Notes: